



THE M7M1

SMALL PROJECT MACHINE

QUICK SPECIFICATIONS



INTERLOCKING BLOCKMAKING MACHINE

- Produces up to 1500 blocks per 8 hour shift*
= $\pm 40\text{m}^2$ of walling/day*
= $\pm 8 \times 50\text{m}^2$ houses/month*
- Single hydraulic block chamber
- Diesel powered engine (electric option available)
- Mobile blockmaking machine
- Intergrated 100ℓ capacity pan mixer

OPTIONAL ACCESSORIES:

- Various moulds available (see reverse page)
- 1 Year maintenance spares pack
- Blockyard tools
- Protective Gear for on site health & safety
- Block Cutter
- Block Tester
- RCB Moulds (Reinforced Concrete Beam)

ADDITIONAL INFO

- Operating Staff: $\pm 8-10$
- Standard 220mm mould fitted

ACCESSORY PRODUCTS:

- Soil pulverizer
- Rotary Sieve for soil preparation

*Based on normal operations & following all Hydraform instructions in manual

THE LEADING ALTERNATIVE BUILDING TECHNOLOGY



ENGINEERED TO CREATE CHANGE



+27 (11) 913 1449



sales@hydraform.com



www.hydraform.com



+27 (11) 913 2840



BLOCKS AND THE USES

BLOCK

DESCRIPTION

BLOCK APPLICATIONS



HYDRAFORM STANDARD 220MM INTERLOCKING BLOCK

This block is used to build load bearing walls using mortar in the super structure, by dry-stacking the blocks on each other in the wall. This block is used for all wall construction in housing and walling. This block will be perfect for ground + 1 construction.

Dimensions: 220mm (W) x 115mm (H) x 230mm (L)



HYDRAFORM STANDARD 180MM INTERLOCKING BLOCK

This 180mm wide, dry-stacking block is used in the construction of load bearing walls for single storey structures only. This block can be used on the first floor of double-storey structures, so as to reduce the weight, but cannot be used in the construction of the ground floor of a double-storey structure. The 180mm block uses 20% less material than the 220mm block.

Dimensions: 180mm (W) x 115mm (H) x 230mm (L)



HYDRAFORM STANDARD 150MM INTERLOCKING BLOCK

This 150mm wide, dry-stacking block is used in the construction of non-load bearing walls for internal walls providing a ring beam is used. This block can be used in the construction of multi-storey structures as an in-fill wall panel between concrete pillars or steel columns. The 150mm block uses 30% less material than the 220mm block.

Dimensions: 150mm (W) x 115mm (H) x 230mm (L)



HYDRAFORM STANDARD 140MM SEMI-INTERLOCKING BLOCK

This 140mm wide block is semi dry-stacking, and a wet cement slurry is poured between the two vertical joints of the blocks. This block is used for internal wall construction and as an in-fill wall panel between concrete pillars or steel columns. The 140mm block uses 36% less material than the 220mm block.

Dimensions: 140mm (W) x 115mm (H) x 230mm (L)



HYDRAFORM LONG BLOCK FOR CORNER CONSTRUCTION

This block is made on any of the Standard Hydraform moulds by double filling the block compression chamber, if the material allows. The long block is used for corner construction and replaces the need for a half block. The daily production of long blocks must be 10% of the daily production of standard blocks.


Dimensions: 150, 180, 220mm (W) x 115mm (H) x 280mm (L)



HYDRAFORM CONDUIT 220MM INTERLOCKING BLOCK

This 220mm wide, dry-stacking block is used to lay the electrical conduit horizontally within the wall structure so that minimal wall chasing is required. This block can also be used in seismic areas (as per engineer's design) to lay steel re-bar within the wall structure to strengthen the structure but also allow enough flexibility to resist collapse during an earthquake.

Dimensions: 220mm (W) x 115mm (H) x 230mm (L)



HYDRAFORM CAPPING 220MM BLOCK

This 220mm wide, dry-stacking block is used for capping of boundary walls and for window sills.

Dimensions: 220mm (W) x 115mm (H) x 230mm (L)



*Based on normal operations & following all Hydraform instructions in manual



ENGINEERED TO CREATE CHANGE



+27 (11) 913 1449



sales@hydraform.com



www.hydraform.com